

WINTPOWER®

WT-R300 300KVA Technical Data sheet



ISO
9001
QUALITY
ASSURANCE

Professional Genset Manufacture On Your Side
FUZHOU WINTPOWER TECHNOLOGY CO., LTD

WT RICARDO KOFO SERIES DIESEL GENERATOR SETS

TECHNICAL SPECIFICATION

KOFO POWERED GENERATOR SETS: WT-R300

Quality Standards

Our diesel generating sets meets the following standards:
GB/T2820, GB1105, YD/T502, ISO3046, ISO8525, ISO8525-3-5-6, EPA

Factory Test

Each our generating sets must be got through 1 hour load test for running 0%, 25%, 50%,75%, 100% and 110% load before dispatch, All protective devices, control functions are simulated and it's system checked, proved and then passed for dispatch. A test certificate can be provided upon request.

MAIN SPECIFICATIONS OF GENERATOR SETS

<i>Diesel Generator Set</i>	
GENSET MODEL NO.	WT-R300
Manufacturer	WINTPOWER China
Rated speed / frequency	1500 rpm / 50 Hz
Continuous output (KW/KVA)	220/275
Standby output (KW/KVA)	240/300
Voltage, Phase and wire	400/230V, 3 Phase and 4 Wires
Rated power factor	0.8 (lagging)
Maximum output current(A)	433A
Dimension(L*W*H)(mm) - open type	2550x900x1650
Weight(kg)	1680kg
Dimension(L*W*H)(mm) - silent type	3300x1100x1500
Rating Definitions (Operation at Altitude ≤1000m, Ambient temperature ≤ 40°C)	
Continuous Power	
These ratings are applicable for supplying continuous electrical power (at variable load) in lieu of commercially purchased power. There is no limitation to the annual hours of operation and this model can supply 10% overload power for 1 hour in 12 hours.	
<i>Diesel Engine</i>	
DIESEL ENGINE MODEL	6126A-260DE (RICARDO KOFO)
Type	Vertical, water cooling, four stoke
Combustion chamber type	Direct injector
Number of cylinders	6
Bore(mm)	126
Stoke(mm)	135
Compression ratio	16:1
Total displacement(L)	10.97
Firing order	1-5-3-6-2-4
Rated power(KW)	260KW/1500RPM

Main specific fuel consumption rate at full load(g/kW.h)	≤215
Cooling method	Forced water cooled
Starting method	Electric
Net mass kg	1090
Overall dimensions(L*W*H) (mm)	2045×900×1693
ALTERNATOR	
ALTERNATOR MODEL	WT314G220 (WT Series)
Maxima Output(kw)	240kw
Excitation	Brushless
Insulation class	H
Protection class	IP23
Efficiency	88.5%
Voltage adjust range	≥±5%
Steady state voltage regulation	≤±0.5%
Voltage Control	AVR AS440
Generating Set Control System HGM6120NC	
<p>AC/DC control panel consisting of:</p> <ul style="list-style-type: none"> ↻ Emergency Stop button ↻ Voltmeter and selector switch ↻ Ammeter and selector switch ↻ Frequency meter ↻ Controller Smartgen HGM6120NC with following (and not restricted to) features: <ul style="list-style-type: none"> ☺ Auto/Manual-Start/Stop ☺ Monitor engine temperature and provides shutdown protection ☺ Monitor engine speed and provides optional shutdown protection ☺ Monitor oil pressure or level and provides shutdown protection ☺ Water temperature display ☺ Alarm output for abnormal operation ☺ Tamper proof engine hours ☺ Front Panel Mounting ☺ Auxiliary shutdown input 	

Available Options:

----Weatherproof Canopy, Soundproof Canopy, Trailers, Automatic mains failure panel, Manual transfer panel, Automatic transfer Panel, Fully Automatic Synchronizing and load Sharing Panel, Manual Synchronizing Panel.

In line with our policy of continuous product development, we reserve our right to change the above specifications without notice.