

WINTPOWER®



WT-C250 Technical Data sheet



Professional Genset Manufacture On Your Side
FUZHOU WINTPOWER TECHNOLOGY CO., LTD.

DIESEL GENERATOR

Powered by Cummins Engine & Stamford Alternator

STANDARD SPECIFICATION

Three phase four wire,output voltage 380/220V,50HZ,between 0.8 lagging,protection capability according with the standard of NEMA1 and IP23.

General Features:

- Δ Composed of Cummins diesel engine and Stamford alternator
- Δ Oil and fuel filter fitted,water separator
- Δ Lube-oil drain valve fitted
- Δ Electric Starter Charge motor 24 VD.C
- Δ Water-cooled
- Δ Baseskid fuel tank
- Δ Auto start
- Δ Optional soundproof and weatherproof canopy
- Δ 3 pole MCCB Delixi breaker
- Δ Operation & Maintenance manual
- Δ Special Integrated Steel Base tank and sprayed overall in gloss enamel paint

Voltage Regulation

- Voltage regulation maintained within $\pm 0.5\%$
- Between 0.8 and 1.0 lagging and unity
- From no load to full load
- At speed droop variation upto 4.5%

Frequency Adjustable Ratio


- Change load from 0-100%,within 1.0%(electric speed regulator),within 4.5%(mechanical speed regulator)

Frequency Undulation

- load from 0-100%,frequency undulation within 0.25%
- No load wire volts max undulation ration\ within 1.8%
- Three Phrase balanced load in the order of 5%

Effect factor of Telecom

- TIF better than 50
- THF to IEC60034 Part 40 better than 2%



50HZ, 1500RPM,3-PHASE 380/220V

Gensets model	Power output(KVA)		Power output (KW)		Cummins Engine Model	Stamford Alternator
	Prime Power	Standby Power	Prime Power	Standby Power		
WT-C250	225	250	180	200	6LTAA8.9-G2	UCDI274J

Note:

- (1) Available in the following voltages:220V-240V AND 380V-415V(440V)-50HZ
- (2) PRP:Prime Power-Continuous duty operation,under variable load 24/24-h-10% overload permissible 1 hour/12hours.
- (3) Rating Definitions (Operation at Altitude $\leq 1000m$, Ambient temperature $\leq 40^{\circ}C$)Continuous Power.These ratings are applicable for supplying continuous electrical power (at variable load) in lieu of commercially purchased power.

Engine & Alternator

ENGINE--Industrial 4 stroke cooled diesel engine complete with air,fuel and oil filters,electric starting and charging equipment,engine protection against low water level.

ALTERNATOR--Brushless,self exciting,self regulation,sreen protected,drip proof rated in accordance with IEC60034.Voltage regulation maintained within $\pm 0.5\%$ from no load to full load.between 0.8 lagging and unity.All standard voltages available.

COOLING--Radiator and colling fan complete with protection guards,designed to cool engine at specified output in air temperatures upto 45 °C.,radiators suitable for higher temperatures are available.Low water level protection fitted as standard.

ELECTRICAL SYSTEM--24V upto.Axial type starter motor,battery charging alternator,high capacity lead acid battery,and battery tray mounted on the generator base frame,and heavy duty interconnecting cable with terminations.

EXHAUST SYSTEM--Heavy duty industrial exhaust silencer with flexible piping.

Technical Data Sheet

Generating sets model:

380/220V,50Hz,1500 rpm

Engine Model:	Cummins 6LTA A8.9G2
Type	6 cylinder,4 cycle diesel
Aspiration	Turbocharged
Bore/Stroke mm	114X145
Compress the ratio	16.6/1
Cooling system	Water-cooled
100% Load Fuel Consumption L/H	53
Engine Speed/Frequency RPM/Hz	1500/50HZ
Rated Output kw/Bhp	220/295
Exhaust air flow (m3/min)	490
Coolant Capacity L	63
Starting System	Electric 24 volt DC
Displacement L	8.3
Lubricant system Capacity L	27.6
Battery Volatge / Capacity	24VDC
Governing Type	Electrical (GAC governor)
Exhaust Gas Temperature °C	541
Exhaust Gas flow m3/min	56.9
Noise level dBA@1m	≤ 80 dBA(canopy type)

Genset Option Features

- Δ Low fuel level alarm shutdown
- Δ Automatic Fuel Filling System
- Δ Engine oil feeding and drain pump
- Δ Auto Transfer Switch(ATS)
- Δ Parallel control panels
- Δ Circuit Breaker MCCB & ACB
- Δ Remote Control Panel
- Δ weatherproof/soundproof Canopy
- Δ Trailer type Gensets

QUALITY STANDARDS

- ISO9001:2020,ISO14001,ISO3046
- ISO8528 BS4999
- BS5514,AS1359,ICE34
- CE Compliance

Gensets Dimensions & Weight

- Open type:L*W*H,mm
2240×980×1820 1500kg
- Enclosure type:L*W*H,mm
3280×1080×1765 2250kg

Alternator Technical data

Stamford UCDI274J

- Δ Bruhless,self exciting
- Δ Class "H" insulation
- Δ Standard degree of protection is IP23
- Δ Self regulating
- Δ With fan cooling
- Δ Resist Humid grease
- Δ AC excitation,roating rectification tube
- Δ Stator grease insulation covered
- Δ Rotator and exciation high polymer,Resist the corruption of oil and acid
- Δ Rotator ballance is in accordance with BS5625 standard 12.5
- Δ High-quality lubrication sealed long-time bearing
- Δ Rotator sillicon steel close tight

Exciter	Brushless
Cooling Fan	Cast alloy aluminum
Bearing	Single,double shielded
Windings	100% copper
Connection Type	Reconnectable
Insulation Type	Class H
Pitch	2/3
Amortisseur Winding	Full
Voltage Regulator	AS440
Voltage Regulator NL-FL	$\pm 0.5\%$
Underspeed Protection	Standard
Overexcitation Protection	IP23
TIF (1960 Weightings)	<50
Exciation System	SHUNT

Control Panel - DEEPSEA7320

The base mounted control panel in a vibration isolated sheet steel enclosure. The control panel is equipped as follows:

- a) Instruments: Analogue Voltmeter, Hours Run Meter, Water pressure Meter.
- b) Controls: Emergency Stop Pushbutton, Voltmeter Phase Selector Switch.
- c) Control module: Standard collocation is DSE7320 Auto start .



DSE7320

Main Features:

- Δ Automatic mains failure
- Δ Engine control, Generator protection
- Δ Built in alarms and warnings
- Δ Remote Start operation available
- Δ Daily / weekly / monthly exerciser
- Δ Weekly operation schedule programs
- Δ Fuel pump control
- Δ ECU control and monitoring
- Δ Mains simulation
- Δ Block heater control
- Δ Field adjustable parameters
- Δ Free MS-Windows Remote monitoring
- Δ LED displays
- Δ Configurable analogue inputs

Sound Attenuated Enclosure/Fuel Tank

Robust Corrosion Resistant Construction

- Δ Black finish stainless steel lock and hinges
- Δ Body made from steel components treated with polyester powder coating

Excellent Access for Maintenance

- Δ two large doors on each side
- Δ radiator fill access plate
- Δ lube oil and cooling water drains pipes to exterior of the enclosure

Security and Safety

- Δ control panel viewing window in a lockable access door
- Δ emergency stop push button (red) mounted on enclosure interior
- Δ cooling fan and battery charging alternator fully guarded
- Δ exhaust silencing system totally enclosed for operator safety

Base Fuel Tank and Accessories

- Δ capacity designed for 8 hours running.
- Δ at least 3 mm thickness 100% steel adopted.
- Δ twice welding inside and outside of all the welding line
- Δ each fuel tank being tested against oil leakage on
- Δ each fuel tank with our factory series number
- Δ fuel tank with necessary drain outlet
- Δ fuel tank with necessary fuel in and back outlet



WINTPOWER, reserves the right to modify the characteristics of its product at any time in order to incorporate the latest technological developments. The information contained in this document may therefore be changed without notice. For more technical data, contact sales@wintpower.com

Manufacture: FUZHOU WINTPOWER TECHNOLOGY CO., LTD.