

WINTPOWER®



WT-C1000 800KW Technical Data sheet



Professional Genset Manufacture On Your Side
FUZHOU WINTPOWER TECHNOLOGY CO., LTD.

WINTPOWER®

DIESEL GENERATOR

Powered by Cummins Engine & Stamford Alternator

STANDARD SPECIFICATION

Three phase four wire, output voltage 380/220V, 50HZ, between 0.8 lagging, protection capability according with the standard of NEMA1 and IP23.

General Features:

- Δ Composed of Cummins diesel engine and Stamford alternator
- Δ Oil and fuel filter fitted, water separator
- Δ Lube-oil drain valve fitted
- Δ Electric Starter Charge motor 24 V.D.C
- Δ Water-cooled
- Δ baseskid fuel tank
- Δ Auto start
- Δ Optional soundproof and weatherproof canopy
- Δ 3 pole MCCB Delixi breaker/Optional ABB
- Δ Operation & Maintenance manual
- Δ Special Integrated Steel Base tank and sprayed overall in gloss enamel paint

Voltage Regulation

- Voltage regulation maintained within $\pm 0.5\%$
- Between 0.8 and 1.0 lagging and unity
- From no load to full load
- At speed droop variation upto 4.5%

Frequency Adjustable Ratio

- Change load from 0-100%, within 1.0% (electric speed regulator), within 4.5% (mechanical speed regulator)

Frequency Undulation

- load from 0-100%, frequency undulation within 0.25%
- No load wire volts max undulation ration\ within 1.8%
- Three Phrase balanced load in the order of 5%

Effect factor of Telecom

- TIF better than 50
- THF to IEC60034 Part 40 better than 2%



50HZ, 1500RPM, 3-PHASE, 380/220V

Gensets model	Power output(KVA)		Power output (KW)		Cummins Engine Model	Stamford Alternator
	PRP	ESP	PRP	ESP		
WT-C1000	900	1000	720	800	KTA38-G2A	HCI 634H

Note:

- (1) Available in the following voltages: 220V-240V AND 380V-415V(440V)-50HZ
- (2) PRP: Prime Power-Continuous duty operation, under variable load 24/24-h-10% overload permissible 1 hour/12hours.
- (3) Rating Definitions (Operation at Altitude $\leq 1000m$, Ambient temperature $\leq 40^{\circ}C$) Continuous Power. These ratings are applicable for supplying continuous electrical power (at variable load) in lieu of commercially purchased power.

Engine & Alternator

ENGINE--Industrial 4 stroke cooled diesel engine complete with air,fuel and oil filters,electric starting and charging equipment,engine protection against low water level.

ALTERNATOR--Brushless,self exciting,self regulation,sreen protected,drip proof rated in accordance with IEC60034.Voltage regulation maintained within $\pm 0.5\%$ from no load to full load.between 0.8 lagging and unity.All standard voltages available.

COOLING--Radiator and colling fan complete with protection guards,designed to cool engine at specified output in air temperatures upto 45°C ,radiators suitable for higher temperatures are available.Low water level protection fitted as standard.

ELECTRICAL SYSTEM--24V upto.Axial type starter motor,battery charging alternator,high capacity lead acid battery,and battery tray mounted on the generator base frame,and heavy duty interconnecting cable with terminations.

EXHAUST SYSTEM--Heavy duty industrial exhaust silencer with flexible piping.

Technical Data Sheet

Generating sets model:

380/220V,50Hz,1500 rpm

Engine Model:	Cummins KTA38G2A	
Type	12 cylinder,4 cycle diesel	
Aspiration	Turbocharged	
Bore/Stroke	mm	159X159
Compress the ratio	13.0:1	
Cooling system	Water-cooled	
100% Load Fuel Consumption	L/H	191
Engine Speed/Frequency	RPM/Hz	1500/50HZ
Standby Output	kw/Bhp	813/1090
Exhaust air flow	(m3/min)	588
Coolant Capacity	L	194
Starting System	Electric 24 volt DC	
Displacement	L	37.8
Lubricant system Capacity	L	135
Battery Volatge / Capacity	24VDC	
Governing Type	Electrical (GAC governor)	
Exhaust Gas Temperature	$^{\circ}\text{C}$	552
Exhaust Gas flow	m3/min	158.6
Noise level	dBA@1m	$\leq 80\text{dBA}(\text{container type})$

Genset Option Features

ΔLow fuel level alarm shutdown
 ΔAutomatic Fuel Filling System
 ΔEngine oil feeding and drain pump
 ΔAuto Transfer Switch(ATS)
 ΔParallel control panels
 ΔCircuit Breaker MCCB & ACB
 ΔRemote Control Panel
 Δweatherproof/soundproof Canopy

ΔTrailer type Gensets

QUALITY STANDARDS

ISO9001:2020,ISO14001,ISO3046
 ISO8528 BS4999
 BS5514,AS1359,ICE34
 CE Compliance

Gensets Dimensions & Weight

Open type:L*W*H,mm
 4370mmX2057mmX2192mm
 Enclosure type:L*W*H,mm
 20FT Container

Alternator Technical data

Stamford HCI 634H

- Δ Bruhxless,self exciting
- Δ Class "H" insulation
- Δ Standard degree of protection is IP23
- Δ Self regulating
- Δ With fan cooling
- Δ Resist Humid grease
- Δ AC excitation,roating rectification tube
- Δ Stator grease insulation covered
- Δ Rotator and exciation high polymer,Resist the corruption of oil and acid
- Δ Rotator ballance is in accordance with BS5625 standard 12.5
- Δ High-quality lubrication sealed long-time bearing
- Δ Rotator sillicon steel close tight

Exciter	Brushless
Cooling Fan	Cast alloy aluminum
Bearing	Single,double shielded
Windings	100% copper
Connection Type	Reconnectable
Insulation Type	Class H
Pitch	2/3
Amortisseur Winding	Full
Voltage Regulator	R250
Voltage Regulator NL-FL	$\pm 0.5\%$
Underspeed Protection	Standard
Overexcitation Protection	IP23
TIF (1960 Weightings)	<50
Exciation System	PMG

Control Panel - DEEPSEA7320

The base mounted control panel in a vibration isolated sheet steel enclosure. The control panel is equipped as follows:

- a) Instruments: Analogue Voltmeter, Hours Run Meter, Water pressure Meter.
- b) Controls: Emergency Stop Pushbutton, Voltmeter Phase Selector Switch.
- c) Control module: Standard collocation is DSE7320 Auto start .



DSE7320

Main Features:

- Δ Automatic mains failure
- Δ Engine control, Generator protection
- Δ Built in alarms and warnings
- Δ Remote Start operation available
- Δ Daily / weekly / monthly exerciser
- Δ Weekly operation schedule programs
- Δ Fuel pump control
- Δ ECU control and monitoring
- Δ Mains simulation
- Δ Block heater control
- Δ Field adjustable parameters
- Δ Free MS-Windows Remote monitoring
- Δ LED displays
- Δ Configurable analogue inputs

Robust Corrosion Resistant Construction

Δ ATS installed inside independent box 800*600*2200mm

Δ Auto transfer switch panel with all light indicator

Excellent Access for Maintenance

Δ two large doors on each side

Δ radiator fill access plate

Δ lube oil and cooling water drains pipes to exterior of the enclosure

Security and Safety

Δ control panel viewing window in a lockable access door

Δ emergency stop push button (red) mounted on enclosure interior

Δ cooling fan and battery charging alternator fully guarded

Δ exhaust silencing system totally enclosed for operator safety

Separated Fuel Tank inside Container and Accessories

Δ capacity designed for 8 hours running.

Δ at least 2mm thickness 100% steel adopted.

Δ twice welding inside and outside of all the welding line

Δ each fuel tank being tested against oil leakage on process

Δ each fuel tank with our factory series number

Δ fuel tank with necessary drain outlet

Δ fuel tank with necessary fuel in and back outlet



WINTPOWER, reserves the right to modify the characteristics of its product at any time in order to incorporate the latest technological developments. The information contained in this document may therefore be changed without notice. For more technical data, contact sales@wintpower.com

Manufacture in China: FUZHOU WINTPOWER TECHNOLOGY CO., LTD.