

WINTPOWER®



WT-C575 Technical Data sheet



Professional Genset Manufacture On Your Side
FUZHOU WINTPOWER TECHNOLOGY CO., LTD.

DIESEL GENERATOR

Powered by Cummins Engine & Leroy Somer Alternator

STANDARD SPECIFICATION

Three phase four wire,output voltage 575V,50HZ,between 0.8 lagging,protection capability according with the standard of NEMA1 and IP23.

General Features:

- ΔComposed of Cummins diesel engine and Leroy Somer alternator
- ΔOil and fuel filter fitted,water separator
- ΔLube-oil drain valve fitted
- ΔElectric Starter Charge motor 24 VD.C
- ΔWater-cooled
- Δ baseskid fuel tank
- ΔAuto start
- ΔOptional soundproof and weatherproof canopy
- Δ 3 pole MCCB Delixi breaker/Optional ABB
- Δ Operation & Maintenance manual
- ΔSpecial Integrated Steel Base tank and sprayed overall in gloss enamel paint

Voltage Regulation

- Voltage regulation maintained within $\pm 0.5\%$
- Between 0.8 and 1.0 lagging and unity
- From no load to full load
- At speed droop variation upto 4.5%

Frequency Adjustable Ratio


- Change load from 0-100%,within 1.0%(electric speed regulator),within 4.5%(mechanical speed regulator)

Frequency Undulation

- load from 0-100%,frequency undulation within 0.25%
- No load wire volts max undulation ration\ within 1.8%
- Three Phrased balanced load in the order of 5%

Effect factor of Telecom

- TIF better than 50
- THF to IEC60034 Part 40 better than 2%



50HZ, 1500RPM,3-PHASE, 575V

Gensets model	Power output(KVA)		Power output (KW)		Cummins Engine Model	Leroy Somer Alternator
	PRP	ESP	PRP	ESP		
WT-C575	525	575	420	460	KTAA19G6A	TAL-A47-E

Note:

(1) Available in the following voltages:220V-240V AND 380V-415V(440V)-50HZ

(2) PRP:Prime Power-Continuous duty operation,under variable load 24/24-h-10% overload permissible 1 hour/12hours.

(3) Rating Definitions (Operation at Altitude $\leq 1000\text{m}$, Ambient temperature $\leq 40^\circ\text{C}$) Continuous Power. These ratings are applicable for supplying continuous electrical power (at variable load) in lieu of commercially purchased power.

Engine & Alternator

ENGINE--Industrial 4 stroke cooled diesel engine complete with air, fuel and oil filters, electric starting and charging equipment, engine protection against low water level.

ALTERNATOR--Brushless, self exciting, self regulation, screen protected, drip proof rated in accordance with IEC60034. Voltage regulation maintained within $\pm 0.5\%$ from no load to full load, between 0.8 lagging and unity. All standard voltages available.

COOLING--Radiator and cooling fan complete with protection guards, designed to cool engine at specified output in air temperatures up to 45°C , radiators suitable for higher temperatures are available. Low water level protection fitted as standard.

ELECTRICAL SYSTEM--24V upto. Axial type starter motor, battery charging alternator, high capacity lead acid battery, and battery tray mounted on the generator base frame, and heavy duty interconnecting cable with terminations.

EXHAUST SYSTEM--Heavy duty industrial exhaust silencer with flexible piping.

Technical Data Sheet

Generating sets model:

575V, 50Hz, 1500 rpm

Engine Model:	Cummins KTAA19G6A	
Type	6 cylinder, 4 cycle diesel	
Aspiration	Turbocharged	
Bore/Stroke	mm	159X159
Compress the ratio	13.0:1	
Cooling system	Water-cooled	
100% Load Fuel Consumption	L/H	168
Engine Speed/Frequency	RPM/Hz	1500/50HZ
Rated Output	kw/Bhp	610/818
Exhaust air flow	(m ³ /min)	588
Coolant Capacity	L	91
Starting System	Electric 24 volt DC	
Displacement	L	18.9
Lubricant system Capacity	L	50
Battery Voltage / Capacity	24VDC	
Governing Type	Electrical (GAC governor)	
Exhaust Gas Temperature	$^\circ\text{C}$	490
Exhaust Gas flow	m ³ /min	119.5
Noise level	dBA@1m	$\leq 80\text{dBA}$ (canopy type)

Genset Option Features

- Δ Low fuel level alarm shutdown
- Δ Automatic Fuel Filling System
- Δ Engine oil feeding and drain pump
- Δ Auto Transfer Switch (ATS)
- Δ Parallel control panels
- Δ Circuit Breaker MCCB & ACB
- Δ Remote Control Panel
- Δ weatherproof/soundproof Canopy
- Δ Trailer type Gensets

QUALITY STANDARDS

- ISO9001:2020, ISO14001, ISO3046
- ISO8528 BS4999
- BS5514, AS1359, ICE34
- CE Compliance

Gensets Dimensions & Weight

- Open type: L*W*H, mm
3280×1305×1950
- Enclosure type: L*W*H, mm
6000×2500×2200

Alternator Technical data

Leroy Somer TAL-A47-E

- Δ Brushless, self exciting
- Δ Class "H" insulation
- Δ Standard degree of protection is IP23
- Δ Self regulating
- Δ With fan cooling
- Δ Resist Humid grease
- Δ AC excitation, rotating rectification tube
- Δ Stator grease insulation covered
- Δ Rotor and excitation high polymer, Resist the corruption of oil and acid
- Δ Rotor balance is in accordance with BS5625 standard

Exciter	Brushless
Cooling Fan	Cast alloy aluminum
Bearing	Single, double shielded
Windings	100% copper
Connection Type	Reconnectable
Insulation Type	Class H
Pitch	2/3
Amortisseur Winding	Full
Voltage Regulator	R205
Voltage Regulator NL-FL	$\pm 0.5\%$
Underspeed Protection	Standard

12.5

Δ High-quality lubrication sealed long-time bearing

Δ Rotator silicon steel close tight

Overexcitation Protection

IP23

TIF (1960 Weightings)

<50

Excitation System

SHUNT

Control Panel- ComAp AMF20

The base mounted control panel in a vibration isolated sheet steel enclosure. The control panel is equipped as follows:

a) Instruments: Analogue Voltmeter, Hours Run Meter, Water pressure Meter.

b) Controls: Emergency Stop Pushbutton, Voltmeter Phase Selector Switch.

c) Control module: Standard collocation ComAp AMF20



ComAp AMF20

Main Features:

- Δ Automatic mains failure
- Δ Engine control, Generator protection
- Δ Built in alarms and warnings
- Δ Remote Start operation available
- Δ Daily / weekly / monthly exerciser
- Δ Weekly operation schedule programs
- Δ Fuel pump control
- Δ Mains simulation
- Δ Block heater control
- Δ Field adjustable parameters
- Δ Free MS-Windows Remote monitoring
- Δ LED displays
- Δ Configurable analogue inputs
- Δ I/O expansion capability
- Δ I/O expansion capability

Robust Corrosion Resistant Construction

Δ Black finish stainless steel lock and hinges

Δ body made from steel components treated with polyester powder coating

Excellent Access for Maintenance

Δ two large doors on each side

Δ radiator fill access plate

Δ lube oil and cooling water drains pipes to exterior of the enclosure

Security and Safety

Δ control panel viewing window in a lockable access door

Δ emergency stop push button (red) mounted on enclosure interior

Δ cooling fan and battery charging alternator fully guarded

Δ exhaust silencing system totally enclosed for operator

Fuel Tank and Accessories

Δ capacity designed for 12 hours running.

Δ at least 3 mm thickness 100% steel adopted.

Δ twice welding inside and outside of all the welding line

Δ each fuel tank being tested against oil leakage on process

Δ each fuel tank with our factory series number

Δ fuel tank with necessary drain outlet

Δ fuel tank with necessary fuel in and back outlet



WINTPOWER, reserves the right to modify the characteristics of its product at any time in order to incorporate the latest technological developments. The information contained in this document may therefore be changed without notice. For more technical data, contact sales@wintpower.com

Manufacture in China: FUZHOU WINTPOWER TECHNOLOGY CO., LTD.